

TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

adds TROTON SPRAY SANDING AID



PRODUCT DESCRIPTION

Matt control lacquer, used as the assistance during grinding, quick-drying.

PHYSICAL AND CHEMICAL PROPERTIES

- Color: black
- Capacity: 500 ml.
- Base: nitro-cellulose binder
- Glass grade: mat
- Efficiency: 3 ÷ 4 m²
- Sandable: after 5 – 10 minutes

VOC CONTENT

VOC = 704,2 [g/l].

The product fulfils the requirements of the European Directive (2004/42/WE), which defines the volatile components content for that products category (cat..B/5) at the level of 840[g/l] for the ready product.

USAGE

- Best processing temperature is $5 \div 30^{\circ}\text{C}$.
- Surface should be clean, dry and degreased.
- Shake before using for 2 minutes and try it on cardboard.
- During lacquering hold aerosol in $25 \div 30$ cm distance from the surface.
- Apply thin layer of sanding aid and leave it until dry.
- Sand the surface until control lacquer is completely removed.
- **Clean the spray nozzle after use!** – Holding the can with the valve pointing downward, press the button emptying the content for about 5 seconds.

Caution: To maintain safety, always follow the instructions given in the Safety Data Sheet for the given product.

STORAGE

Product should be stored in dry, cool, ventilated place, away from fire and direct sunlight.

EXPIRY DATE

5 years from the production date.

All information are based upon the precise laboratory studies and many years of experience. The good market position does not release us from the constant supervision of our products quality. However we are not responsible for the final effects of the improper storage or application of our products, as well as for work inconsistent with the good craft practice.

TROTON Sp. z o.o.
Ząbrowo, Poland