



Mipa Acryl-Lackspray

Klarlack

Product Information

gb - 1/0612

Art.Nr.: 21450 + Gloss degree

Mipa Acryl-Lackspray Klarlack is a high quality, fast drying, colourless overcoat for 2-layer basecoats. Also suited for clear-over-base applications of blank iron and non-ferrous metals. The original appearance of the substrate remains unaffected.



Substrate:

2-layer basecoats, aluminium, copper, brass, stainless steel



Pretreatment / Cleansing:

Clean with Mipa Silikonentferner

Special characteristics:

High UV-protection
Good weathering and scratch resistance
Non-yellowing
Lightfast
Excellent levelling
Permanent protection against water, oxidation, exhaust fumes as well as diluted acids and alkali.

Colour / Gloss:

colourless
high gloss (0002) / mat (0001)

Application:



Shake can vigorously prior to use!

Spraying:



Spray to test - Spraying distance approx. 20 - 30 cm
2 - 3 coats. Dry film thickness 40 - 50 µm.

Flash-off:



3 - 5 min. between the spraying operations

After use:



After use, turn can upside down and spray until the valve is clean, this prevents the valve from clogging up.

Drying times:



Drying:

Dust dry:

5 - 10 min. / 20°C

Set to touch:

20 - 30 min. / 20°C

Full hardness:

2 h / 20°C

Process conditions:

from +10°C and up to 80% relative air humidity

Storage:

In tightly closed original containers 2 years shelf life. Keep cool and dry.

VOC- content:

EU limiting value for the product (cat. B/e): 840 g/l

This product contains max. 700 g/l VOC [5.84 lbs/gal]

Safety instructions:

see the safety data sheet

The data sheet is for information purpose only! The information given is in accordance to our knowledge up to the latest standards and is based on years of experience in the manufacture of our products. The information is non binding and without guarantee.